

Safety Data Sheet

Printing date 02/04/2021

Revised On 02/04/2021

1 Identification of the substance and manufacturer

Trade name: 025802 GREEN ZINC PHOSPHATE PRIMER
Product code: MM00025802
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Eye Irrit. 2A H319 Causes serious eye irritation.
 Skin Sens. 1 H317 May cause an allergic skin reaction.
 STOT SE 3 H336 May cause drowsiness or dizziness.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

79-20-9	methyl acetate	25-50%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
110-19-0	Isobutyl Acetate	1-5%
1330-20-7	xylene (mix)	1-5%
64-17-5	ethyl alcohol	1-5%
67-64-1	Acetone	1-5%
64742-89-8	VM&P Naphtha	1-5%
64742-47-8	Mineral Spirits	1-5%
67-56-1	methanol	0.17%
108-31-6	maleic anhydride	0.03%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 (Contd. on page 2)

Safety Data Sheet

Printing date 02/04/2021

Revised On 02/04/2021

Trade name: 025802 GREEN ZINC PHOSPHATE PRIMER

(Contd. of page 1)

After swallowing: Rinse out mouth and then drink plenty of water.
Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects: Dizziness

Indication of any immediate medical attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

Protective equipment for firefighters: A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures: Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up: Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling: Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.
Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****79-20-9 methyl acetate**

PEL (USA) Long-term value: 610 mg/m³, 200 ppm

REL (USA) Short-term value: 760 mg/m³, 250 ppm
Long-term value: 610 mg/m³, 200 ppm

TLV (USA) Short-term value: 757 mg/m³, 250 ppm
Long-term value: 606 mg/m³, 200 ppm

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm
(EX)

110-19-0 Isobutyl Acetate

PEL (USA) Long-term value: 700 mg/m³, 150 ppm

REL (USA) Long-term value: 700 mg/m³, 150 ppm

TLV (USA) Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

1330-20-7 xylene (mix)

PEL (USA) Long-term value: 435 mg/m³, 100 ppm

REL (USA) Short-term value: 655 mg/m³, 150 ppm
Long-term value: 435 mg/m³, 100 ppm

TLV (USA) Short-term value: 651 mg/m³, 150 ppm
Long-term value: 434 mg/m³, 100 ppm
BEI

64-17-5 ethyl alcohol

PEL (USA) Long-term value: 1900 mg/m³, 1000 ppm

REL (USA) Long-term value: 1900 mg/m³, 1000 ppm

TLV (USA) Short-term value: 1880 mg/m³, 1000 ppm

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm

REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 1187 mg/m³, 500 ppm
Long-term value: 594 mg/m³, 250 ppm
BEI

(Contd. on page 3)

Safety Data Sheet

Printing date 02/04/2021

Revised On 02/04/2021

Trade name: 025802 GREEN ZINC PHOSPHATE PRIMER

(Contd. of page 2)

67-56-1 methanol

PEL (USA)	Long-term value: 260 mg/m ³ , 200 ppm
REL (USA)	Short-term value: 325 mg/m ³ , 250 ppm Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV (USA)	Short-term value: 328 mg/m ³ , 250 ppm Long-term value: 262 mg/m ³ , 200 ppm Skin; BEI

108-31-6 maleic anhydride

PEL (USA)	Long-term value: 1 mg/m ³ , 0.25 ppm
REL (USA)	Long-term value: 1 mg/m ³ , 0.25 ppm
TLV (USA)	Long-term value: 0.01* mg/m ³ , 0.0025* ppm DSEN, RSEN;*inhalable fraction + vapor

Ingredients with biological limit values:**1330-20-7 xylene (mix)**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

67-64-1 Acetone

BEI (USA)	50 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----------	--

67-56-1 methanol

BEI (USA)	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----------	---

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Avoid contact with the eyes and skin.
Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-110 °C (-166 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.7 Vol %
Upper Explosion Limit:	16 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
Water:	0.0 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
--------------------	--------------------------------

(Contd. on page 4)

Safety Data Sheet

Printing date 02/04/2021

Revised On 02/04/2021

Trade name: 025802 GREEN ZINC PHOSPHATE PRIMER

Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.	(Contd. of page 3)
Chemical stability:	Not fully evaluated.	
Possibility of hazardous reactions:	No dangerous reactions known.	
Incompatible materials:	No further relevant information available.	
Hazardous decomposition:	No dangerous decomposition products known.	

11 Toxicological information**LD/LC50 values that are relevant for classification:****79-20-9 methyl acetate**

Oral LD50 6,970 mg/kg (rat)

110-19-0 Isobutyl Acetate

Oral LD50 4,763 mg/kg (rbt)

1330-20-7 xylene (mix)

Oral LD50 8,700 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rbt)

Inhalative LC50/4 h 6,350 mg/l (rat)

64-17-5 ethyl alcohol

Oral LD50 7,060 mg/kg (rat)

Inhalative LC50/4 h 20,000 mg/l (rat)

67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rbt)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950
DOT UN1950
 UN1950
DOT Aerosols, flammable
ADR 1950 Aerosols
Transport hazard class(es):
Class 2.1
Marine pollutant: No
 Symbol (fish and tree)
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

1330-20-7 xylene (mix)

7779-90-0 zinc phosphate

(Contd. on page 5)

Safety Data Sheet

Printing date 02/04/2021

Revised On 02/04/2021

Trade name: 025802 GREEN ZINC PHOSPHATE PRIMER

(Contd. of page 4)

1314-13-2 zinc oxide

Toxic Substances Control Act**(TSCA):**

All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List**(DSL):**

All ingredients are listed or exempted.

Consumer Product Safety**Commission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

1333-86-4 Carbon black

108-10-1 methyl isobutyl ketone

Prop 65 chemicals known to cause birth defects or reproductive harm:

67-56-1 methanol

108-10-1 methyl isobutyl ketone

EPA:

110-19-0 Isobutyl Acetate

D

1330-20-7 xylene (mix)

I

7779-90-0 zinc phosphate

D, I, II

67-64-1 Acetone

I

1314-13-2 zinc oxide

D, I, II

16 Other information**Contact:**

Regulatory Affairs