



Safety Data Sheet

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 31-8013-0 | Version Number: | 2.01 |
| Issue Date: | 02/08/16 | Supersedes Date: | 10/29/14 |

SECTION 1: Identification

1.1. Product identifier

3M(TM) Marine Adhesive Sealant 4200 White; PN 05260

Product Identification Numbers

| ID Number | UPC | ID Number | UPC |
|----------------|-----|----------------|-----|
| 62-5579-1632-7 | | 62-5579-5232-2 | |
| 62-5579-5235-5 | | | |

1.2. Recommended use and restrictions on use

Recommended use

Sealant

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Respiratory Sensitizer: Category 1.

Skin Sensitizer: Category 1.

Carcinogenicity: Category 2.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Health Hazard |

Pictograms



Hazard Statements

Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.

Causes damage to organs:
sensory organs |

Causes damage to organs through prolonged or repeated exposure:
nervous system |

May cause damage to organs through prolonged or repeated exposure:
sensory organs |

Precautionary Statements

General:

Keep out of reach of children.

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
In case of inadequate ventilation wear respiratory protection.
Wear protective gloves and eye/face protection.
Do not eat, drink or smoke when using this product.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
IF exposed or concerned: Get medical advice/attention.

Storage:

Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

2% of the mixture consists of ingredients of unknown acute dermal toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|------------|------------------------|
| Phenol Alkylsulfonate | 70775-94-9 | 20 - 40 Trade Secret * |
| Urethane Polymer | 51447-37-1 | 20 - 40 Trade Secret * |
| Poly(vinyl Chloride) | 9002-86-2 | 20 - 30 Trade Secret * |
| Titanium Dioxide | 13463-67-7 | 1 - 5 Trade Secret * |
| Calcium Oxide | 1305-78-8 | 1 - 3 Trade Secret * |
| Xylene | 1330-20-7 | < 2 Trade Secret * |
| Ethylbenzene | 100-41-4 | < 0.6 Trade Secret * |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | < 0.3 Trade Secret * |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8 | < 0.2 Trade Secret * |

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

DO NOT USE WATER

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Condition

| | |
|--------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Cyanide | During Combustion |
| Oxides of Nitrogen | During Combustion |

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|--------------------------------------|------------|-------------------------|-----------------------------|------------------------------|
| Ethylbenzene | 100-41-4 | ACGIH | TWA:20 ppm | A3: Confirmed animal carcin. |
| Ethylbenzene | 100-41-4 | CMRG | TWA:25 ppm;STEL:75 ppm | |
| Ethylbenzene | 100-41-4 | OSHA | TWA:435 mg/m3(100 ppm) | |
| FREE ISOCYANATES | 101-68-8 | Manufacturer determined | TWA:0.005 ppm;STEL:0.02 ppm | |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8 | ACGIH | TWA:0.005 ppm | |
| p,p'-Methylenebis(phenyl isocyanate) | 101-68-8 | OSHA | CEIL:0.2 mg/m3(0.02 ppm) | |
| Calcium Oxide | 1305-78-8 | ACGIH | TWA:2 mg/m3 | |

| | | | | |
|--|------------|-------|---|--------------------------------|
| Calcium Oxide | 1305-78-8 | OSHA | TWA:5 mg/m3 | |
| Xylene | 1330-20-7 | ACGIH | TWA:100 ppm;STEL:150 ppm | A4: Not class. as human carcin |
| Xylene | 1330-20-7 | CMRG | TWA:50 ppm;STEL:75 ppm | |
| Xylene | 1330-20-7 | OSHA | TWA:435 mg/m3(100 ppm) | |
| Titanium Dioxide | 13463-67-7 | ACGIH | TWA:10 mg/m3 | A4: Not class. as human carcin |
| Titanium Dioxide | 13463-67-7 | CMRG | TWA(as respirable dust):5 mg/m3 | |
| Titanium Dioxide | 13463-67-7 | OSHA | TWA(as total dust):15 mg/m3 | |
| 3-(Trimethoxysilyl)propyl glycidyl ether | 2530-83-8 | CMRG | TWA:5 ppm | |
| DUST, INERT OR NUISANCE | 9002-86-2 | OSHA | TWA(as total dust):15 mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3);TWA(respirable fraction):5 mg/m3 | |
| Poly(vinyl Chloride) | 9002-86-2 | ACGIH | TWA(respirable fraction):1 mg/m3 | A4: Not class. as human carcin |

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---|
| General Physical Form: | Solid |
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | White thixotropic paste, slight odor. |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>No Data Available</i> |
| Boiling Point | <i>Not Applicable</i> |
| Flash Point | No flash point |
| Evaporation rate | <i>Not Applicable</i> |
| Flammability (solid, gas) | Not Classified |
| Flammable Limits(LEL) | <i>Not Applicable</i> |
| Flammable Limits(UEL) | <i>Not Applicable</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 1.18 g/ml |
| Specific Gravity | 1.18 [<i>Details: Water = 1</i>] |
| Solubility in Water | Nil |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | ≥ 750 °F |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | <i>No Data Available</i> |
| Hazardous Air Pollutants | 2.4 % weight [<i>Test Method: Calculated</i>] |
| VOC Less H2O & Exempt Solvents | 36 g/l [<i>Test Method: calculated SCAQMD rule 443.1</i>] |
| VOC Less H2O & Exempt Solvents | 3.0 % [<i>Test Method: calculated SCAQMD rule 443.1</i>] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Water

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| <u>Ingredient</u> | <u>CAS No.</u> | <u>Class Description</u> | <u>Regulation</u> |
|-------------------|----------------|-------------------------------|---|
| Ethylbenzene | 100-41-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |
| Titanium Dioxide | 13463-67-7 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Additional Information:

Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE > 5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE > 50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE > 5,000 mg/kg |
| Urethane Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Urethane Polymer | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Phenol Alkylsulfonate | Dermal | Rat | LD50 > 1,000 mg/kg |
| Phenol Alkylsulfonate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Poly(vinyl Chloride) | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Poly(vinyl Chloride) | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Titanium Dioxide | Dermal | Rabbit | LD50 > 10,000 mg/kg |
| Titanium Dioxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 6.82 mg/l |
| Titanium Dioxide | Ingestion | Rat | LD50 > 10,000 mg/kg |
| Calcium Oxide | Ingestion | Rat | LD50 > 2,500 mg/kg |
| Xylene | Dermal | Rabbit | LD50 > 4,200 mg/kg |
| Xylene | Inhalation-Vapor (4 hours) | Rat | LC50 29 mg/l |
| Xylene | Ingestion | Rat | LD50 3,523 mg/kg |
| Ethylbenzene | Dermal | Rabbit | LD50 15,433 mg/kg |
| Ethylbenzene | Inhalation-Vapor (4 hours) | Rat | LC50 17.4 mg/l |
| Ethylbenzene | Ingestion | Rat | LD50 4,769 mg/kg |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Dermal | Rabbit | LD50 4,000 mg/kg |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 5.3 mg/l |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Rat | LD50 7,010 mg/kg |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation-Vapor | | LC50 estimated to be 10 - 20 mg/l |
| p,p'-Methylenebis(phenyl isocyanate) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.369 mg/l |
| p,p'-Methylenebis(phenyl isocyanate) | Ingestion | Rat | LD50 31,600 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-------------------------|---------------------------|
| Poly(vinyl Chloride) | Professional judgment | No significant irritation |
| Titanium Dioxide | Rabbit | No significant irritation |
| Calcium Oxide | Human | Corrosive |
| Xylene | Rabbit | Mild irritant |
| Ethylbenzene | Rabbit | Mild irritant |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Rabbit | Mild irritant |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Irritant |

| | | |
|--|------|--|
| | tion | |
|--|------|--|

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-------------------------|---------------------------|
| Titanium Dioxide | Rabbit | No significant irritation |
| Calcium Oxide | Rabbit | Corrosive |
| Xylene | Rabbit | Mild irritant |
| Ethylbenzene | Rabbit | Moderate irritant |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Rabbit | Corrosive |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|--|-------------------------|--|
| Titanium Dioxide | Human and animal | Not sensitizing |
| Ethylbenzene | Human | Not sensitizing |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Guinea pig | Some positive data exist, but the data are not sufficient for classification |
| p,p'-Methylenebis(phenyl isocyanate) | official classification | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|--------------------------------------|---------|-------------|
| p,p'-Methylenebis(phenyl isocyanate) | Human | Sensitizing |

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|--|
| Poly(vinyl Chloride) | In Vitro | Not mutagenic |
| Titanium Dioxide | In Vitro | Not mutagenic |
| Titanium Dioxide | In vivo | Not mutagenic |
| Calcium Oxide | In Vitro | Not mutagenic |
| Xylene | In Vitro | Not mutagenic |
| Xylene | In vivo | Not mutagenic |
| Ethylbenzene | In vivo | Not mutagenic |
| Ethylbenzene | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 3-(Trimethoxysilyl)propyl glycidyl ether | In vivo | Not mutagenic |
| 3-(Trimethoxysilyl)propyl glycidyl ether | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| p,p'-Methylenebis(phenyl isocyanate) | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|----------------------|---------------|-------------------------|--|
| Poly(vinyl Chloride) | Not Specified | Rat | Some positive data exist, but the data are not sufficient for classification |
| Titanium Dioxide | Ingestion | Multiple animal species | Not carcinogenic |
| Titanium Dioxide | Inhalation | Rat | Carcinogenic |
| Xylene | Dermal | Rat | Not carcinogenic |
| Xylene | Ingestion | Multiple animal species | Not carcinogenic |
| Xylene | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |

| | | | |
|--|------------|-------------------------|--|
| Ethylbenzene | Inhalation | Multiple animal species | Carcinogenic |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Dermal | Mouse | Not carcinogenic |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|---------------|--|-------------------------|-----------------------|--------------------------------|
| Poly(vinyl Chloride) | Not Specified | Not toxic to development | Mouse | NOAEL Not available | during gestation |
| Xylene | Inhalation | Some positive female reproductive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | occupational exposure |
| Xylene | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Mouse | NOAEL Not available | during organogenesis |
| Xylene | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL Not available | during gestation |
| Ethylbenzene | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 4.3 mg/l | prematuring & during gestation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Not toxic to female reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Not toxic to male reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 3,000 mg/kg/day | during organogenesis |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | Some positive developmental data exist, but the data are not sufficient for classification | Rat | NOAEL 0.004 mg/l | during organogenesis |

Lactation

| Name | Route | Species | Value |
|--------|-----------|---------|--|
| Xylene | Ingestion | Mouse | Does not cause effects on or via lactation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------|------------|-----------------------------------|--|-------------------------|---------------------|-----------------------|
| Calcium Oxide | Inhalation | respiratory irritation | May cause respiratory irritation | Not available | NOAEL Not available | occupational exposure |
| Xylene | Inhalation | auditory system | Causes damage to organs | Rat | LOAEL 6.3 mg/l | 8 hours |
| Xylene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Xylene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human | NOAEL Not available | |
| Xylene | Inhalation | eyes | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 3.5 mg/l | not available |
| Xylene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Multiple animal species | NOAEL Not available | |

| | | | | | | |
|--------------------------------------|------------|-----------------------------------|--|-------------------------|---------------------|----------------|
| Xylene | Ingestion | eyes | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 250 mg/kg | not applicable |
| Ethylbenzene | Inhalation | central nervous system depression | May cause drowsiness or dizziness | Human | NOAEL Not available | |
| Ethylbenzene | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Human and animal | NOAEL Not available | |
| Ethylbenzene | Ingestion | central nervous system depression | May cause drowsiness or dizziness | Professional judgement | NOAEL Not available | |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|----------------------|------------|--|--|-------------------------|-----------------------|-----------------------|
| Poly(vinyl Chloride) | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL 0.013 mg/l | 22 months |
| Titanium Dioxide | Inhalation | respiratory system | Some positive data exist, but the data are not sufficient for classification | Rat | LOAEL 0.01 mg/l | 2 years |
| Titanium Dioxide | Inhalation | pulmonary fibrosis | All data are negative | Human | NOAEL Not available | occupational exposure |
| Xylene | Inhalation | nervous system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.4 mg/l | 4 weeks |
| Xylene | Inhalation | auditory system | May cause damage to organs through prolonged or repeated exposure | Rat | LOAEL 7.8 mg/l | 5 days |
| Xylene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL Not available | |
| Xylene | Inhalation | heart endocrine system hematopoietic system muscles kidney and/or bladder respiratory system | All data are negative | Multiple animal species | NOAEL 3.5 mg/l | 13 weeks |
| Xylene | Ingestion | auditory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 900 mg/kg/day | 2 weeks |
| Xylene | Ingestion | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1,500 mg/kg/day | 90 days |
| Xylene | Ingestion | liver | Some positive data exist, but the data are not sufficient for classification | Multiple animal species | NOAEL Not available | |
| Xylene | Ingestion | heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system | All data are negative | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| Ethylbenzene | Inhalation | kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 1.1 mg/l | 2 years |
| Ethylbenzene | Inhalation | liver | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 1.1 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | hematopoietic system | Some positive data exist, but the data are not sufficient for | Rat | NOAEL 3.4 mg/l | 28 days |

| | | | classification | | | |
|--|------------|---|--|-------------------------|-----------------------|-----------|
| Ethylbenzene | Inhalation | auditory system | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 2.4 mg/l | 5 days |
| Ethylbenzene | Inhalation | endocrine system | Some positive data exist, but the data are not sufficient for classification | Mouse | NOAEL 3.3 mg/l | 103 weeks |
| Ethylbenzene | Inhalation | bone, teeth, nails, and/or hair muscles | All data are negative | Multiple animal species | NOAEL 4.2 mg/l | 90 days |
| Ethylbenzene | Inhalation | heart immune system respiratory system | All data are negative | Multiple animal species | NOAEL 3.3 mg/l | 2 years |
| Ethylbenzene | Ingestion | liver kidney and/or bladder | Some positive data exist, but the data are not sufficient for classification | Rat | NOAEL 680 mg/kg/day | 6 months |
| 3-(Trimethoxysilyl)propyl glycidyl ether | Ingestion | heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | All data are negative | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| p,p'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |

Aspiration Hazard

| Name | Value |
|--------------|-------------------|
| Xylene | Aspiration hazard |
| Ethylbenzene | Aspiration hazard |

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M transportation classifications are based on product formulation, packaging, 3M policies and 3M understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for U.S. ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact manufacturer for more information

311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

| <u>Ingredient</u> | <u>C.A.S. No</u> | <u>% by Wt</u> |
|---------------------------------|------------------|--------------------|
| Xylene | 1330-20-7 | Trade Secret < 2 |
| Xylene (Benzene, 1,2-dimethyl-) | 1330-20-7 | < 2 |
| Xylene (Benzene, 1,3-dimethyl-) | 1330-20-7 | < 2 |
| Xylene (Benzene, 1,4-dimethyl-) | 1330-20-7 | < 2 |
| Xylene (Benzene, dimethyl-) | 1330-20-7 | < 2 |
| Ethylbenzene | 100-41-4 | Trade Secret < 0.6 |

15.2. State Regulations

Contact manufacturer for more information

California Proposition 65

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Classification</u> |
|-------------------|-------------------|-----------------------|
| Ethylbenzene | 100-41-4 | Carcinogen |

WARNING: This product contains a chemical known to the State of California to cause cancer.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA.

Contact manufacturer for more information

15.4. International Regulations

Contact manufacturer for more information

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 31-8013-0 | Version Number: | 2.01 |
| Issue Date: | 02/08/16 | Supercedes Date: | 10/29/14 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com