

MSDS - SILOXANE LUBRICANT

1. SUPPLIER INFORMATION:

Supplier Name - Hitex Insulation (Ningbo) Co., Ltd

Supplier Address - Room 1502, Europe Business Building, NSBD, Ningbo, China

Emergency Contact - 0086-574-27898220

Fax telephone - 0086-574-27898230

2. IDENTIFICATION OF CHEMICALS AND ENTERPRISES:

2.1. Product Name: Siloxane Lubricant

2.2 Classification of Hazardous Chemicals: Organic Functional Siloxanes

3.COMPOSITION INFORMATION:

3.1. chemical categories: mixture

3.2. physical form: liquid

3.3. appearance color: emerald color

3.4. main purposes: Defoamer, hydraulic oil, high-grade lubricating oil, packing surface treatment agent and demulsifier

4. THE HAZARDOUS INFORMATION:

Possible health effects

Eyes: Will not irritate the eyes

Skin: Does not irritate the skin

Inhalation: No data available

Carcinogenicity: Unknown cancer toxicity

5. FIRST AID MEASURES:

Eye contact: Flush eyelids with plenty of water for at least 15 minutes. If irritation develops or persists, seek medical attention immediately.

Skin contact: Flush with plenty of water for at least 15 minutes. If irritation develops or persists, seek medical attention immediately.

Re-use, wash the contaminated clothing.

Inhalation: Although you do not know what can cause respiratory problems, if you feel difficulty breathing, immediately breathe fresh air or oxygen.

Ingestion: for a long time, do not cause vomiting, drink into the 1 ~ 2 cups of water for medical treatment.

6. FIRE FIGHTING MEASURES:

Flammability: Non-flammable

Limits of combustion in air: LEL: N / A UEL: N / A

Extinguishing media: When the flame is extended, use chemical foam, carbon dioxide or sprinkler fire, sprinkle water to reduce the temperature of the exposed solvent.

Ignition and Leakage Hazards: Unusual hazards in case of fire.

Fire-fighting instructions: Wear self-contained breathing apparatus and protective clothing.

7. LEAKAGE CONTINGENCY:

Personal protection: hand protection, eye protection.

Environmental Precautions: Never dispose of in a natural stream. (Biological treatment equipment)

Cleaning methods: Absorbent material absorption treatment, UV-ray treatment, direct sunlight or acid gas treatment.

8. DISPOSAL AND STORAGE:

Disposal: Do not use special methods.

Storage: Keep sealed, stored in dry, low temperature, the sun can not direct the place.

Storage temperature should not be higher than 60 ° C.

Fire and explosion: Do not use special methods.

9. EXPOSURE CONTROL / PERSONAL PROTECTION:

engineering control:

Generally good ventilation conditions are adequate to control airborne transmission.

Eye / face protection,

The substance does not have a defined exposure limit.

Eye contact may be possible. Eye protection is recommended.

Skin protection

It is not necessary to use the same protective equipment as described on the label.

Respiratory protection

Under normal conditions of use ventilation in good condition, you can not wear protective equipment.

Exposure guidelines: Not available.

14. DISPOSAL:

Waste Disposal: Dispose of the waste in accordance with local, state, and national requirements.

15. TRANSPORT INFORMATION:

Product Logo: Siloxane Lubricant

D.O.T Shipping Name: N / A

Technical shipping name: N / A

Hazard class: N / A

UN Number: N / A

D.O.T Label: N / A

D.O.T Posted: N / A

Volume rating: N / A

16. REGULATORY INFORMATION:

EEC Symbols and Hazard Symbols: None

WHMIS Hazard symbol: None