

# **Safety Data Sheet**

Issuing Date 01-Jul-2014 Revision Date 01-Jul-2014 Version 1

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name Sierra NMMA FC-W Catalyst Compatible 10W-30 Motor Oil

Other means of identification

Product Code(s) 18-9420CAT-2, 18-9420CAT-4, 18-9420CAT-7

Synonyms No information available

Recommended use of the chemical and restrictions on use
Recommended Use Engine oil, Lubricant.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address Sierra International 1 Sierra Place Litchfield, IL 62056

Emergency telephone number

Company Phone Number 877-663-8396 Company Emergency Phone (618) 542-5431

Number

Emergency telephone number Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

#### Classification

**OSHA Regulatory Status** 

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation Category 2A

### Label elements

### **EMERGENCY OVERVIEW**

### WARNING

Hazard statements

Causes serious eye irritation



Appearance Amber colored liquid

Physical state viscous liquid

Odor Mild petroleum odor

Revision Date 01-Jul-2014

### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

### Hazards not otherwise classified (HNOC)

Causes mild skin irritation.

Other information

Unknown Aquatic Toxicty

1.14% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Common NameHydrocarbon Lubricating Fluid.Chemical FamilyPetroleum hydrocarbon mixture.

Chemical name	CAS-No	Weight %	Trade secret
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	81.4	*
Mineral Oils	MIXTURE	0-16	*
Zinc O,O,O',O'-tetrakis(1,3-dimethylbutyl) bis(phosphorodithioate)	2215-35-2	0.53-1.05	*
Reaction products of Benzeneamine, N-phenyl with nonene (branched)	36878-20-3	0.53-1.05	*
Phenol, dodecyl-, branched	121158-58-5	0.01-0.09	*
Diphenylamine	122-39-4	0.01-0.09	*
Toluene	108-88-3	0.002	*

The mineral oil mixture contained may be described by one or more of the following: CAS No. 64742-54-7, Distillates (petroleum), hydrotreated heavy paraffinic; CAS No. 64742-65-0, Distillates (petroleum), solvent-dewaxed heavy paraffinic; CAS No. 64742-55-8, Distillates (petroleum), hydrotreated light paraffinic; CAS No. 64742-56-9, Distillates (petroleum), solvent-dewaxed light paraffinic.

### 4. FIRST AID MEASURES

#### First aid measures

General advice No hazards which require special first aid measures.

Eye contact Flush eyes for 30 minutes with water. Get medical attention if irritation persists.

**Skin contact** Wash off immediately with soap and plenty of water.

**Inhalation** Move exposed persons to fresh air. Consult medical personal if breathing issues occur.

**Ingestion** Do NOT induce vomiting. Consult a physician.

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Revision Date 01-Jul-2014

#### Suitable extinguishing media

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Foam. Water can be used to keep surrounding materials cool.

Small Fires Always use personal safety equipment. Follow appropriate personal safety procedures, and

extinguishing media.

**Large Fires** Contact emergency personnel.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

### Specific hazards arising from the chemical

Combustible material.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal protection** Avoid contact with the skin and the eyes. Eye protection or face shield should be used if

material is used under conditions that increase the chances of splattering. Wash skin with soap and water if contact occurs. Launder soiled clothing. If spilled, take caution, as

material can cause surfaces to become very slippery.

Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Cover with earth, sand, or other non-combustible material followed with plastic sheets to

minimize spreading or contact with rain.

Methods for cleaning up Excess liquid material can be collected using a scoop or shovel and stored for recycling or

disposal. Prevent material from entering drains or waterways.

### 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing. Eye protection or face shield should be used if

material is used under conditions that increase the chances of splattering. If contact is made, wash skin with soap and water. Launder soiled clothing. Maximum handling temperature is 70 degrees C (158 F). It is recommended to pump or transfer material at

ambient temperature.

### Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat and sources of ignition. Keep containers closed when not in use.

Follow first aid measures if contact occurs, and spill procedures if spill occurs. For packaged material: Store in a cool dry area. For bulk material: store in cool dry area. Always follow local, state, and federal guidlines for storage of material for amount stored.

Incompatible Products Strong oxidizing agents.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

**Exposure guidelines**This product does not contain any hazardous materials with occupational exposure limits

established by the region specific regulatory bodies.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Diphenylamine 122-39-4	TWA: 10 mg/m <sup>3</sup>	-	TWA: 10 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³

### **Appropriate engineering controls**

Engineering Controls Showers

Eyewash stations Ventilation systems.

### Individual protection measures, such as personal protective equipment

Eye/face Protection If splashes are likely to occur, wear:. Goggles. Eye/face Protection.

**Skin and body protection**Long sleeved clothing. Protective gloves can be worn, if material comes in contact with skin

wash with soap and water.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Cleveland open cup (COC)

provided in accordance with current local regulations.

**General Hygiene Considerations** Remove and wash contaminated clothing before re-use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state viscous liquid

AppearanceAmber colored liquidOdorMild petroleum odorColorOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No information available
Melting point/freezing point No information available
Boiling Point/Range No information available

Flash point > 93.3 °C / > 200 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific gravity 0.86-0.88

Water solubility No information available

Solubility in other solventsNo information availablePartition coefficientNo information available

Autoignition temperature

Decomposition temperatureNo information availableKinematic viscosity15.6 @100C mm2/sDynamic viscosityNo information availableExplosive propertiesNo information availableOxidizing propertiesNo information available

Other information

Softening pointNo information availableVOC ContentNo information availableDensityNo information availableBulk densityNo information available

### 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under normal conditions.

### **Possibility of Hazardous Reactions**

None under normal processing.

**Hazardous polymerization** Hazardous polymerization does not occur.

### **Conditions to avoid**

Excessive heat. High energy sources of ignition.

### **Incompatible materials**

Strong oxidizing agents.

### **Hazardous decomposition products**

None known based on information supplied.

### 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

Inhalation Inhalation of vapors in high concentration may cause irritation of respiratory system.

**Eye contact** Avoid contact with eyes. May cause irritation.

**Skin contact** Prolonged skin contact may defat the skin and produce dermatitis. May cause irritation.

**Ingestion** Do NOT taste or swallow.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Reaction products of Benzeneamine, N-phenyl with nonene (branched) 36878-20-3	> 5000 mg/kg(Rat)	-	-
Phenol, dodecyl-, branched 121158-58-5	= 2100 mg/kg (Rat)	= 5 mL/kg(Rabbit)	-
Diphenylamine 122-39-4	= 1165 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	-

Information on toxicological effects

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye irritation Irritating to eyes.

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	Group 1	-	Х
Toluene 108-88-3	-	Group 3	-	-

Reproductive toxicity Product is or contains a chemical which is a known or suspected reproductive hazard.

**Developmental toxicity**Contains ingredients that have suspected developmental hazards.

STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Aspiration hazard Not Applicable.

Numerical measures of toxicity - Product Information

Unknown Aquatic Toxicty 1.14% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document

### 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

May cause long lasting harmful effects to aquatic life

9.098% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Petroleum distillates, hydrotreated heavy paraffinic 64742-54-7	-	5000: 96 h Oncorhynchus mykiss mg/L LC50	1000: 48 h Daphnia magna mg/L EC50
Reaction products of Benzeneamine, N-phenyl with nonene (branched) 36878-20-3	-	1000: 96 h Pimephales promelas mg/L LC50 semi-static	14 - 28: 96 h Mysidopsis bahia mg/L LC50
Phenol, dodecyl-, branched 121158-58-5	-	0.14: 96 h Oncorhynchus clarki mg/L LC50	-
Diphenylamine 122-39-4	1.5: 72 h Scenedesmus subspicatus mg/L EC50	3.47 - 4.14: 96 h Pimephales promelas mg/L LC50 flow-through	1.69 - 2.46: 48 h Daphnia magna mg/L EC50

5.46 - 9.83: 48 h Daphnia magna 433: 96 h Pseudokirchneriella 15.22 - 19.05: 96 h Pimephales Toluene 108-88-3 subcapitata mg/L EC50 12.5: 72 promelas mg/L LC50 flow-through mg/L EC50 Static 11.5: 48 h h Pseudokirchneriella subcapitata 12.6: 96 h Pimephales promelas Daphnia magna mg/L EC50 mg/L EC50 static mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static

#### Persistence and degradability

No information available.

### **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Diphenylamine 122-39-4	3.5
Toluene 108-88-3	2.65

Other adverse effects No information available

### 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Waste Disposal Method Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Diphenylamine 122-39-4	(hazardous constituent - no waste number)	Included in waste streams: F039, K083, K104	-	-
Toluene 108-88-3	waste number U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	-

Chemical name	RCRA - Halogenated	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
	Organic Compounds			

Toluene	-	- Toxic waste -
108-88-3		waste number F025
		Waste description:
		Condensed light ends, spent
		filters and filter aids, and
		spent desiccant wastes from
		the production of certain
		chlorinated aliphatic
		hydrocarbons, by free
		radical catalyzed processes.
		These chlorinated aliphatic
		hydrocarbons are those
		having carbon chain lengths
		ranging from one to and
		including five, with varying
		amounts and positions of
		chlorine substitution.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Diphenylamine 122-39-4	Toxic
Toluene 108-88-3	Toxic; Ignitable

### 14. TRANSPORT INFORMATION

**DOT** Not regulated

<u>IATA</u> PETROLEUM LUBRICATING OIL; NOT REGULATED AS DANGEROUS GOODS FOR

TRANSPORT UNDER ICAO TI OR IATA DGR

### 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Does not comply **DSL/NDSL** Does not comply Does not comply **EINECS/ELINCS** Does not comply **ENCS IECSC** Does not comply **KECL** Does not comply Does not comply **PICCS AICS** Does not comply

#### <u>Legend:</u>

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### U.S. Federal Regulations

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	SARA 313 - Threshold Values %
Diphenylamine - 122-39-4	1.0
Toluene - 108-88-3	1.0

### SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X
108-88-3				

CERCLA
This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

### **U.S. State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Prop. 65	
Toluene - 108-88-3	Developmental	
Female Reproductive		

### **U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Diphenylamine 122-39-4	Х	X	X
Toluene 108-88-3	X	X	Х

### U.S. EPA Label Information

EPA Pesticide registration number Not Applicable

16. OTHER INFORMATION				
<u>NFPA</u>	Health hazards 1	Flammability 1	Instability 0	Physical and Chemical Hazards -
HMIS	Health hazards 1	Flammability 1	Physical hazards 0	Personal protection X
Issuing Date 01-Jul-2014		014		

Sierra NMMA FC-W Catalyst Compatible 10W-30 Motor Oil

Revision Date 01-Jul-2014

Revision Date Revision Note

01-Jul-2014

Revision Note Not Applicable <u>Disclaimer</u>

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**