

# **SAFETY DATA SHEET**

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 11-May-2020 Version 5

### 1. IDENTIFICATION

**Product identifier** 

Product Name 98H HIGH TACK GASKET SEALANT 4 FL.OZ

Other means of identification

Product Code 80062

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

### Details of the supplier of the safety data sheet

### **Manufacturer Address**

ITW Permatex, Inc. 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

# 2. HAZARDS IDENTIFICATION

### Classification

### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

### Label elements

Emergency Overview
--------------------

Signal	word
<u>Signal</u> Dange	r

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Suspected of damaging fertility or the unborn child

May cause respiratory irritation

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



Appearance Red Physical state Liquid Odor Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground and bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use non-sparking tools

Take action to prevent static discharges

Keep cool

Wear protective clothing, gloves, and eye protection or face shield

### **Precautionary Statements - Response**

If exposed or concerned: Get medical advice/attention

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

IN CASE OF FIRE: Use CO2, dry chemical, or foam to extinguish.

# **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

# **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

# Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

Toxic to aquatic life with long lasting effects.

Unknown acute toxicity 9.496 % of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
ACETONE	67-64-1	25 - <50%
N-HEXANE	110-54-3	10 - <25%
ROSIN	8050-09-7	10 - <25%

#### 4. FIRST AID MEASURES

#### **Description of first aid measures**

General advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and

shoes.

Eye contact In case of contact with substance, immediately flush skin or eyes with running water for at

least 20 minutes.

**Skin contact** Wash skin with soap and water.

**Inhalation** Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion IF SWALLOWED:. Call a physician or poison control center immediately. Do NOT induce

vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

### Most important symptoms and effects, both acute and delayed

**Symptoms** May cause allergic skin reaction.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, CO2, water spray or regular foam, Water spray, fog or regular foam, Use water spray or fog; do not use straight streams

#### Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient

#### Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapor explosion hazard

indoors, outdoors or in sewers. Those substances designated with a "P" may polymerize explosively when heated or involved in a fire. Runoff to sewer may create fire or explosion hazard. Substance may be transported hot.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All **Personal precautions** 

equipment used when handling the product must be grounded. Do not touch or walk

through spilled material. Stop leak if you can do it without risk.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

**Methods for containment** A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth,

sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for

later disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Handle in accordance with good industrial hygiene and safety practice. Avoid breathing Advice on safe handling

vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric **Storage Conditions** 

motors and static electricity). Store locked up.

Strong oxidizing agents Incompatible materials

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

**Exposure Guidelines** 

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ACETONE	TWA: 250 ppm	TWA: 1000 ppm	IDLH: 2500 ppm

67-64-1	STEL: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	-
		(vacated) STEL: 2400 mg/m <sup>3</sup> The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors.	
		(vacated) STEL: 1000 ppm	
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	IDLH: 1100 ppm
110-54-3	Sk*	TWA: 1800 mg/m <sup>3</sup>	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 180 mg/m <sup>3</sup>
		(vacated) TWA: 180 mg/m <sup>3</sup>	
ROSIN	TWA: 0.001 mg/m³ total resin acids	(vacated) TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup> Formaldehyde
8050-09-7	inhalable particulate matter	Formaldehyde	
	dermal sensitizer;respiratory		
	sensitizer		

NIOSH IDLH Immediately Dangerous to Life or Health

#### **Appropriate engineering controls**

Engineering Controls Showers

Eyewash stations Ventilation systems

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

**Respiratory protection**Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as

appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of

equipment, work area and clothing is recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Red
Odor Solvent

Odor threshold No information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point
Boiling point / boiling range
Flash point
No information available

Evaporation rate > 1 Ether = 1

Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: 13.0%
Lower flammability limit: 2.0%
Vapor pressure 400 mm Hg

Vapor density 2.5 Air = 1

Relative density 0.872

Water solubility Partially soluble

Solubility(ies) No information available
Partition coefficient No information available

**Autoignition temperature** No information available Hyphen No information available

Kinematic viscosity No information available **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

Other information

No information available Softening point Molecular weight No information available **Density** No information available **Bulk density** No information available SADT (self-accelerating No information available

decomposition temperature)

# 10. STABILITY AND REACTIVITY

Reactivity

No information available Not applicable

Chemical stability

Stable under normal conditions

### Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

# **Hazardous decomposition products**

Carbon oxides

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure if inhaled. May

cause drowsiness or dizziness.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact. Skin contact

Ingestion Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and

pneumonitis.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m <sup>3</sup> (Rat) 8 h
N-HEXANE 110-54-3	= 25 g/kg (Rat)	= 3000 mg/kg ( Rabbit )	= 48000 ppm (Rat) 4 h
ROSIN 8050-09-7	= 7600 mg/kg (Rat) = 3000 mg/kg (Rat)	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

IARC (International Agency for Research on Cancer) Group 3 - Not classifiable as a human carcinogen

Target organ effects Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system,

Skin, Thyroid.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 8262 mg/kg
ATEmix (dermal) 8049 mg/kg
ATEmix (inhalation-dust/mist) 178.2 mg/l
ATEmix (inhalation-vapor) 186367 mg/l

### 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

#### **Ecotoxicity**

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

#### **Mobility**

No information available.

Chemical name	Partition coefficient
ACETONE	-0.24
67-64-1	
N-HEXANE	4
110-54-3	
ROSIN	7.7
8050-09-7	

#### Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

### Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001, U002

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
ACETONE	Ignitable
67-64-1	
N-HEXANE	Toxic
110-54-3	Ignitable

### 14. TRANSPORT INFORMATION

DOT

UN/ID No 1133

Proper shipping name Adhesives, Limited Quantity (LQ)

Transport hazard class(es) **Packing Group** 

This product contains a chemical which is listed as a marine pollutant according to DOT. Marine pollutant

**Emergency Response Guide** 128

Number

**IATA** 

**UN** number or ID number ID 8000

Proper shipping name Consumer commodity

Transport hazard class(es) **ERG** Code 9L

**IMDG** 

UN number or ID number 1133

Proper shipping name Adhesives, Limited Quantity (LQ)

Transport hazard class(es) 3 **Packing Group** Ш **EmS-No** 

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to

IMDG/IMO.

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Not determined **ENCS** Not determined **IECSC** Complies **KECI** Complies **PICCS** Complies **AICS** Not determined

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0
SARA 311/312 Hazard Categories	
Acute health hazard	Yes
Chronic Health Hazard	Yes

Chronic Health Hazard

Yes
Fire hazard

Yes
Sudden release of pressure hazard

No
Reactive Hazard

No

### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances	Reportable Quantity (RQ)
		RQs	
ACETONE	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
N-HEXANE	5000 lb	-	RQ 5000 lb final RQ
110-54-3			RQ 2270 kg final RQ

# **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals:

_	The product contains are remarking a representation of the contains and th	
	Chemical name	California Proposition 65
Ī	N-HEXANE	Developmental
1	110-54-3	
Ī	RHODAMINE	Carcinogen
١	81-88-9	

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
RHODAMINE	X	X	X
81-88-9			

#### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### **WHMIS Hazard Class**

B2 - Flammable liquid, D2B - Toxic materials

### 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 -

Health hazards 2 Flammability 3 Physical hazards 0 Personal protection B

Revision Date 11-May-2020

#### **Disclaimer**

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular

purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

**End of Safety Data Sheet** 

Page 10/10