



Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 08/06/2015

Date of issue: 08/06/2015

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Water-Based Waterproofing

Product Code: 822XX

Intended Use of the Product

Water repellent

Name, Address, and Telephone of the Responsible Party

Company

Star brite Inc.

4041 SW 47th Avenue

Fort Lauderdale, FL 33314

(954)587-6280

www.starbrite.com

Emergency Telephone Number

Emergency Number : US: (800) 424-9300; International: (703) 527-3887 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Not classified

Label Elements

GHS-US Labeling No labeling applicable

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Repeated or prolonged exposure may damage the liver and kidneys.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Isopropyl alcohol	(CAS No) 67-63-0	0.5 - 1.5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Dimethylol-5,5-dimethylhydantoin	(CAS No) 6440-58-0	0.1 - 1	Acute Tox. 4 (Oral), H302
2-Methoxyethanol	(CAS No) 109-86-4	<0.1	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Repr. 1B, H360

*A range of concentration as prescribed by Controlled Products Regulations has been used where necessary, due to varying composition. The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER or doctor/physician if you feel unwell.

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

Most Important Symptoms and Effects Both Acute and Delayed

General: None expected under normal conditions of use.

Inhalation: May cause respiratory irritation.

Skin Contact: May cause mild skin irritation.

Eye Contact: May cause slight irritation to eyes.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Do not breathe fumes from fires or vapors from decomposition. Do not allow run-off from firefighting to enter drains or water courses.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: No special measures required.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. Concerning disposal elimination after cleaning, see item 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Fluorine. Metals.

Specific End Use(s) Water repellent

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Isopropyl alcohol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)
Alberta	OEL STEL (mg/m ³)	984 mg/m ³
Alberta	OEL STEL (ppm)	400 ppm
Alberta	OEL TWA (mg/m ³)	492 mg/m ³
Alberta	OEL TWA (ppm)	200 ppm
British Columbia	OEL STEL (ppm)	400 ppm
British Columbia	OEL TWA (ppm)	200 ppm
Manitoba	OEL STEL (ppm)	400 ppm
Manitoba	OEL TWA (ppm)	200 ppm
New Brunswick	OEL STEL (mg/m ³)	1230 mg/m ³
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (mg/m ³)	983 mg/m ³
New Brunswick	OEL TWA (ppm)	400 ppm
Newfoundland & Labrador	OEL STEL (ppm)	400 ppm
Newfoundland & Labrador	OEL TWA (ppm)	200 ppm
Nova Scotia	OEL STEL (ppm)	400 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nunavut	OEL STEL (mg/m ³)	1228 mg/m ³
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (mg/m ³)	983 mg/m ³
Nunavut	OEL TWA (ppm)	400 ppm
Northwest Territories	OEL STEL (mg/m ³)	1228 mg/m ³
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (mg/m ³)	983 mg/m ³
Northwest Territories	OEL TWA (ppm)	400 ppm
Ontario	OEL STEL (ppm)	400 ppm
Ontario	OEL TWA (ppm)	200 ppm
Prince Edward Island	OEL STEL (ppm)	400 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Québec	VECD (mg/m ³)	1230 mg/m ³
Québec	VECD (ppm)	500 ppm

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Québec	VEMP (mg/m ³)	985 mg/m ³
Québec	VEMP (ppm)	400 ppm
Saskatchewan	OEL STEL (ppm)	400 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
Yukon	OEL STEL (mg/m ³)	1225 mg/m ³
Yukon	OEL STEL (ppm)	500 ppm
Yukon	OEL TWA (mg/m ³)	980 mg/m ³
Yukon	OEL TWA (ppm)	400 ppm
2-Methoxyethanol (109-86-4)		
USA ACGIH	ACGIH TWA (ppm)	0.1 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA OSHA	OSHA PEL (TWA) (mg/m ³)	80 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	25 ppm
USA OSHA	Limit value category (OSHA)	prevent or reduce skin absorption
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.3 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	0.1 ppm
USA IDLH	US IDLH (ppm)	200 ppm
Alberta	OEL TWA (mg/m ³)	0.3 mg/m ³
Alberta	OEL TWA (ppm)	0.1 ppm
British Columbia	OEL TWA (ppm)	0.1 ppm
Manitoba	OEL TWA (ppm)	0.1 ppm
New Brunswick	OEL TWA (mg/m ³)	16 mg/m ³
New Brunswick	OEL TWA (ppm)	5 ppm
Newfoundland & Labrador	OEL TWA (ppm)	0.1 ppm
Nova Scotia	OEL TWA (ppm)	0.1 ppm
Nunavut	OEL STEL (mg/m ³)	115 mg/m ³
Nunavut	OEL STEL (ppm)	35 ppm
Nunavut	OEL TWA (mg/m ³)	78 mg/m ³
Nunavut	OEL TWA (ppm)	25 ppm
Northwest Territories	OEL STEL (mg/m ³)	115 mg/m ³
Northwest Territories	OEL STEL (ppm)	35 ppm
Northwest Territories	OEL TWA (mg/m ³)	78 mg/m ³
Northwest Territories	OEL TWA (ppm)	25 ppm
Ontario	OEL TWA (ppm)	0.1 ppm
Prince Edward Island	OEL TWA (ppm)	0.1 ppm
Québec	VEMP (mg/m ³)	16 mg/m ³
Québec	VEMP (ppm)	5 ppm
Saskatchewan	OEL STEL (ppm)	8 ppm
Saskatchewan	OEL TWA (ppm)	5 ppm
Yukon	OEL STEL (mg/m ³)	120 mg/m ³
Yukon	OEL STEL (ppm)	35 ppm
Yukon	OEL TWA (mg/m ³)	80 mg/m ³
Yukon	OEL TWA (ppm)	25 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Not generally required. The use of personal protective equipment may be necessary as conditions warrant.

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Off white
Odor	: Characteristic
Odor Threshold	: Not available
pH	: 7
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: > 100 °C (212 °F)
Flash Point	: > 100 °C (212 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.004 (at 20 °C)
Solubility	: Emulsifiable.
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Fluorine. Metals.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Fluorine compounds. Hydrogen fluoride.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

ID50 and IC50 Data: Not available

Skin Corrosion/Irritation: Not classified

pH: 7

Serious Eye Damage/Irritation: Not classified

pH: 7

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: Not classified

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: May cause mild skin irritation.

Symptoms/Injuries After Eye Contact: May cause slight irritation to eyes.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

ID50 and IC50 Data:

Isopropyl alcohol (67-63-0)	
ID50 Oral Rat	4710 mg/kg
ID50 Dermal Rabbit	4059 mg/kg
IC50 Inhalation Rat	72600 mg/m ³ (Exposure time: 4 h)
Dimethylol-5,5-dimethylhydantoin (6440-58-0)	
ID50 Oral Rat	1572 mg/kg
2-Methoxyethanol (109-86-4)	
ID50 Oral Rat	2370 mg/kg
ID50 Dermal Rabbit	1280 mg/kg
IC50 Inhalation Rat	1478 ppm (Exposure time: 7 h)
ATE US (gases)	4,500.00 ppmV/4h
ATE US (vapors)	11.00 mg/l/4h
ATE US (dust, mist)	1.50 mg/l/4h
Isopropyl alcohol (67-63-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Isopropyl alcohol (67-63-0)	
IC50 Fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	1000 mg/l (Exposure time: 96 h - Species: Desmodesmus subspicatus)
IC 50 Fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Other Aquatic Organisms 2	1000 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
Dimethylol-5,5-dimethylhydantoin (6440-58-0)	
IC50 Fish 1	514 mg/l (Freshwater [96h static] Species: Oncorhynchus mykiss)
2-Methoxyethanol (109-86-4)	
IC50 Fish 1	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
IC 50 Fish 2	9650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
Persistence and Degradability	
Water-Based Waterproofing	
Persistence and Degradability	Not established.
Bioaccumulative Potential	
Water-Based Waterproofing	
Bioaccumulative Potential	Not established.
Isopropyl alcohol (67-63-0)	
Log Pow	0.05 (at 25 °C)
2-Methoxyethanol (109-86-4)	
Log Pow	-0.85

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance With ICAO/IATA/DOT/TDG/IMDG

UN Number Not regulated for transport.

UN Proper Shipping Name Not regulated for transport.

Transport Hazard Class(es) Not regulated for transport.

Additional Information Not available

Marine Pollutant: No

Transport by sea Not regulated for transport.

Air transport Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Isopropyl alcohol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.

SARA Section 313 - Emission Reporting

1.0 % (only if manufactured by the strong acid process, no supplier notification)

Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2-Methoxyethanol (109-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

EPA TSCA Regulatory Flag

S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule.

SARA Section 313 - Emission Reporting

1.0 %

US State Regulations

2-Methoxyethanol (109-86-4)

U.S. - California - Proposition 65 - Developmental Toxicity

WARNING: This product contains chemicals known to the State of California to cause birth defects.

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

WARNING: This product contains chemicals known to the State of California to cause (Male) reproductive harm.

Isopropyl alcohol (67-63-0)

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute

U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic

U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)

U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)

U.S. - Connecticut - Volatile Substances

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)

U.S. - Idaho - Occupational Exposure Limits - TWAs

RTK - U.S. - Massachusetts - Right To Know List

U.S. - Massachusetts - Toxics Use Reduction Act

U.S. - Michigan - Occupational Exposure Limits - STELs

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - TWAs
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - City of Austin - Aerosol Paint and Glue Restrictions
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs

2-Methoxyethanol (109-86-4)

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Acute
U.S. - California - SCAQMD - Toxic Air Contaminants - Non-Cancer Chronic
U.S. - California - Toxic Air Contaminant List (AB 1807, AB 2728)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (30 min)
U.S. - Connecticut - Hazardous Air Pollutants - HLVs (8 hr)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
RTK - U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TEELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Hazardous Substance List

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List
RTK - U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - Skin Designations
U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - Oregon - Permissible Exposure Limits - Skin Designations
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - California - Safer Consumer Products - Initial List of Candidate Chemicals and Chemical Groups
RTK - U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
RTK - U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 25 Feet to Less Than 40 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 40 Feet to Less Than 75 Feet
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights 75 Feet or Greater
U.S. - Wisconsin - Hazardous Air Contaminants - All Sources - Emissions From Stack Heights Less Than 25 Feet

Canadian Regulations

Water-Based Waterproofing

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

Isopropyl alcohol (67-63-0)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Dimethylol-5,5-dimethylhydantoin (6440-58-0)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	---

2-Methoxyethanol (109-86-4)

Listed on the Canadian DSL (Domestic Substances List)

Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 0.1 %

WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	--

Water-Based Waterproofing

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 08/06/2015

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.


GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Repr. 1B	Reproductive toxicity Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H360	May damage fertility or the unborn child

NFPA Health Hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA Fire Hazard : 0 - Materials that will not burn.

NFPA Reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Party Responsible for the Preparation of This Document

Starbrite®

Phone Number: (954)587-6280

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2