1. IDENTIFICATION

1.1. PRODUCT IDENTIFIER USED ON LABEL:

- 1.1.1. MERCURY QUICKLEEN ENGINE & FUEL SYSTEM CLEANER
- 1.2. OTHER MEANS OF IDENTIFICATION:
 - 1.2.1. QUICKLEEN ENGINE & FUEL SYSTEM CLEANER
 - 1.2.2. 184-6094KC, Parts: 92-8M0058711; 92-8M0058691; 92-8M0048211; 92-8M0047931
- 1.3. RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE:
 - 1.3.1. PETROLEUM LUBRICATING OIL
 - 1.3.2. NO OTHER USES RECOMMENDED
- 1.4. NAME, ADDRESS, AND TELEPHONE NUMBER OF THE CHEMICAL MANUFACTURE R, IMPORTER, OR OTHER RESPONSIBLE PARTY:

1.4.1.

Mercury Marine

P.O. Box 1939 Fond du Lac, WI 54935 United States of America

Product Information

General Information: +1 (920) 929-5000

1.5. **EMERGENCY PHONE NUMBER:**

1.5.1.

Emergency Response

North America: CHEMTREC (800) 424-9300 after 5:00pm CST Or +17035273887

2. HAZARD(S) IDENTIFICATION

- 2.1. WARNING! Harmful or fatal if swallowed. Causes eye irritation. Vapor harmful.
- 2.2. Inhalation: May cause irritation to the nose, throat and respiratory tract. Inhalation of high concentrations of vapors may cause respiratory tract irritation and central nervous depression. Symptoms may include headache, nausea, dizziness, and drowsiness. Continued inhalation may result in unconsciousness or death.

- 2.3. Eye Contact: May cause eye irritation. Symptoms may include stinging, tearing, redness and swelling of eyes.
- 2.4. Skin Contact: May cause skin irritation. Symptoms may include dryness, itching, a burning sensation, redness, cracking and swelling depending on the extent of exposure. May be harmful if absorbed through the skin in toxic amounts and cause systemic effects.
- 2.5. Ingestion: May cause gastrointestinal distress. Symptoms include irritation to the mouth, throat and stomach and gastrointestinal disturbances such as nausea, vomiting or diarrhea and effects similar to those described in the Inhalation section. Aspiration of this product into the lungs during ingestion, gagging or vomiting may cause lung damage, which can be fatal.
- 2.6. Chronic Effects: Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling the contents may be harmful or fatal. Prolonged or repeated dermal exposure to this product can cause skin dermatitis characterized by red, dry, scaly skin.
- 2.7. Target Organs: Not Determined
- 2.8. This product does not contain carcinogens or potential carcinogens as listed by IARC or NTP

3. Composition/information on ingredients

3.1. The chemical name and concentration (exact percentage) or concentration ranges of all ingredients which are classified as health hazards in accordance with paragraph (d) of §1910.1200:

3.1.1.

COMPONENTS	CAS Number	EU Number	Concentration	Carcinogen
			(%)	
Petroleum distillates,	64742-47-8	265-149-8	50-70	
hydrotreated light				
Alkylphenol polyoxyalkyl	Proprietary	Proprietary	10-20	
alkylamine				
Petroleum distillates, light	64742-95-6	265-199-0	10-20	
aromatic				
1,2,4-Trimethylbenzene	95-63-6	202-436-9	1-10	
1,3,5-Trimethylbenzene	108-67-8	203-604-4	1-10	
Cumene	98-82-8	202-704-5	<1	*

4. FIRST AID MEASURES

4.1. Eye Contact:

4.1.1. Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated

water into unaffected eye or onto the face. Call poison control center, hospital emergency room, or physician immediately.

4.2. Ingestion:

4.2.1. NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 2 to 8 oz. (60 to 240 ml) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Immediately obtain medical advice.

4.3. Skin Contact:

4.3.1. As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Quickly and gently blot or brush away excess chemical. Immediately wash with lukewarm, gently flowing water and non-abrasive soap for 15-20 minutes. Immediately obtain medical advice. Completely decontaminate clothing, shoes and leather goods before reuse or discard.

4.4. Inhalation:

4.4.1. This product is combustible/flammable. Take proper precautions (e.g. remove any sources of ignition).

Remove source of contamination or move victim to fresh air. Keep victim quiet and warm until emergency help arrives.

4.5. Note to Physician:

4.5.1. There is no specific antidote for effects from overexposure to this material. Treatment should be directed at the control of symptoms and the clinical condition.

5. FIRE FIGHTING MEASURES

5.1. **Flash Point**: 105°F (41°C)

5.2. Fire Fighting Instructions:

5.2.1. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Fire fighters should be protected from potential explosions hazards while extinguishing the fire. Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Containers of this material may build up pressure if exposed to heat (fire). Use water spray to cool fire-exposed containers. Use water spray to disperse vapors if a spill or leak has not ignited. DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

5.3. Extinguishing Media:

5.3.1. Use alcohol foam, dry chemical, carbon dioxide or any Class B fire extinguishing agent. Water may be unsuitable for extinguishing fires. Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

5.4. Hazardous Combustion Products:

5.4.1. See section 10 for potential decomposition products.

6. ACCIDENTAL RELEASE MEASURES

6.1. Personal & Environmental Precautions:

6.1.1. Remove sources of ignition immediately. Stop Flow of material if safe to do so. Contain spill and keep out of water sources. Ventilate area. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal using non-sparking tools. Follow personal protective equipment recommendations found in section 8. Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including: the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill. Never exceed any occupational exposure limits.

6.2. Methods of Containment & Clean-up and Other Information:

6.2.1. This product, if released in large enough quantities, may need to be reported to the US Coast Guard National Response Center at 1-800-424-8802. Contain spills with dikes and absorbents (sand, earth, dry chemical absorbent) to prevent migration and entry into waterways.

7. HANDLING AND STORAGE

7.1. Handling:

7.1.1. Keep container closed and upright when not in use. To prevent generation of static discharges, use bonding/grounding connection when transferring material. Vapors may accumulate and travel to distant ignition sources and flashback. Extinguish all sources of ignition including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Since empty containers may retain product residue and flammable, observe precautions even after container is emptied. Do not cut, puncture, or weld on or near empty containers. Do not smoke where product is used or stored. Avoid contact with eyes, skin or clothing. Avoid inhalation (vapor, mist, dust or fume). Use only with adequate ventilation. Observe good personal hygiene practices and recommended procedures. Wash Thoroughly after handling.

7.2. Storage:

7.2.1. Store in areas/buildings designed to comply with OSHA 1910.106. Store away from sources of ignition and heat. Keep containers closed when not in use. Store in cool, well ventilated space away from incompatible materials.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

8.1. Exposure Limits:

Chemical Name	CAS Number	Z-1 PEL	Z-2 PEL	ACGIH TLV
----------------------	-------------------	---------	---------	-----------

SAFETY DATA SHEET-MERCURY QUICKLEEN ENGINE & FUEL

SYSTEM CLEANER

Petroleum distillates,	64742-47-8		
hydrotreated light			
Alkylphenol polyoxyalkyl	Proprietary		
alkylamine			
Petroleum distillates, light	64742-95-6		
aromatic			
1,2,4-Trimethylbenzene	95-63-6		25 PPM
1,3,5-Trimethylbenzene	108-67-8		25 PPM
Cumene	98-82-8	245 MGM3(50	50 PPM
		ppm)	

8.2. Engineering Measures:

8.2.1. Use adequate ventilation to maintain airborne concentrations at levels below permissible or recommended occupational exposure limits

8.3. Eye/Face Protection:

8.3.1. Wear chemical-resistant glasses and/or goggles and a face shield when eye and face contact is possible due to splashing or spraying of material.

8.4. Skin Protection:

8.4.1. Chemical-resistant, flexible gloves (Viton®), neoprene, nitrile or equal) to prevent contact. Gloves should be rinsed and remove immediately after use. Wash hands after removing gloves. Wear chemical-resistant clothing (e.g. apron, pants, coveralls) and safety footwear as appropriate.

8.5. Respiratory Protection:

8.5.1. Respiratory protection may be necessary under certain use conditions. Under such conditions, an appropriate, properly fitted NIOSH-approved respirator must be worn. If respirators are used, a program should be instituted to assure compliance with 29 CFR 1910.34 and 42. CFR 84.

8.6. General Hygiene Considerations

8.6.1. Facilities utilizing this material should be equipped with an eyewash station and safety shower. Thoroughly clean shoes and wash contaminated clothes before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Properties:

9.1.1. Physical State	Liquid
9.1.2. Appearance	Clear Liquid
9.1.3. Odor	Hydrocarbon
9.1.4. pH	Not applicable

SAFETY DATA SHEET-MERCURY QUICKLEEN ENGINE & FUEL

SYSTEM CLEANER

9.1.5. **Boiling Point** Not determined

9.1.6. **Flash Point** 105°F (41°C)

9.1.7. **Solubility in Water** Insoluble

9.1.8. Specific Gravity ...797

9.1.9. Weight per Gallon (LB/GAL) 6.64

9.1.10. **Evaporation Rate (BUAC=1):** Not determined

9.1.11. Volatile by Weight (including water Not determined

and exempt compounds) (%)

9.1.12. **Volatile Organic Content (VOC)**Not determined

9.1.13. Viscosity @ 40°C Not determined

9.1.14. Viscosity @ 100°C Not determined

10.STABILITY AND REACTIVITY

10.1. Stability:

10.1.1. Stable under normal conditions

10.2. Incompatibility:

10.2.1. Oxidizing and reducing agents. Keep away from heat, sparks and open flames

10.3. Hazardous Decomposition Products:

10.3.1. Carbon monoxide, carbon dioxide, oxides of nitrogen and other toxic organic compounds.

11. TOXICOLOGY INFORMATION

11.1. Toxicological evaluation of this product as a whole has not been performed.

12.ECOLOGICAL INFORMATION

12.1.1. Ecological evaluation of this material has not been performed; however do not allow the product to be released to the environment without governmental approval.permits.

13. DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET-MERCURY QUICKLEEN ENGINE & FUEL

SYSTEM CLEANER

13.1. Waste Disposal:

13.1.1. Waste from this material may be a listed and/or characteristic hazardous waste. Dispose of material, contaminated absorbent, container and unused contents in accordance with local, state, and federal regulations.

14.TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

14.1. ROAD AND RAIL

- 14.1.1. This product is not regulated by the U.S. DOT when shipped by ground in containers <119 gallons
- 14.1.2. DOT Hazard Class: 3
- 14.1.3. **DOT Proper Shipping Name**: Combustible liquid, n.o.s. (petroleum distillates) for containers >119 gal.
- 14.1.4. DOT Packing Group: III
- 14.1.5. **DOT UN Number**: NA1993

14.2. Air

- 14.2.1. IATA Hazard Class: 3
- 14.2.2. IATA Proper Shipping Name: Flammable liquid, n.o.s. (petroleum distillates)
- 14.2.3. IATA Packing Group: III 14.2.4. IATA UN Number: UN1993

14.3. **Vessel**

- 14.3.1. IMDG Hazard Class: 3
- 14.3.2. IMDG Proper Shipping Name: Flammable liquid, n.o.s. (petroleum distillates)
- 14.3.3. IMDG Packing Group: III 14.3.4. IMDG UN Number: UN1993

15. REGULATORY INFORMATION

- 15.1. **EPA Registration Number**: Not Applicable 15.2. **Pest Registration Act Number**: Not Applicable
- 15.3. **Other**: Not Determined 15.4. **Chemical Regulations**

Chemical Name	CAS Number	TSCA 12B	SARA 313	TSCA	DSL	EINECS	Prop 65	Whmis
Petroleum distillates, hydrotreated	C4742 47 0							
light	64742-47-8			*	*			
Alkylphenol polyoxyalkyl								
alkylamine	Proprietary							
Petroleum distillates, light aromatic	64742-95-6			*	*	*		*
1,2,4-Trimethylbenzene	95-63-6		*	*	*	*		*
1,2,5-Trimethylbenzene	108-67-8			*	*	*		
Cumene	98-82-8		*	*	*	*	*	*

16.OTHER INFORMATION

16.1.

HAZARD RANKINGS						
HMIS Health 2 NFPA Health						
HMIS Flammability	2	NFPA Flammability	2			
HMIS Physical Hazard	0	NFPA Instability/Reactivity	0			

- 16.2. Date of preparation: April 22, 2015
- 16.3. This product may be formulated with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Mercury Marine must rely on information provided by those materials manufacturers or distributors.

16.4. MANUFACTURER DISCLAIMER:

16.4.1. The data presented herein is based upon tests and information, which we believe to be reliable.

However, users should make their own investigations to determine the suitability of the information for their particular purpose