

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

1. Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

1.2. Relevant identified uses of substance or mixture and uses advised against

Recommended use: General industrial application

1.3. Details of the supplier of the safety data sheet

Identification of the supplier: JXTG Nippon Oil & Energy Corporation

Address: 1-2, Otemachi 1-Chome, Chiyoda-ku, Tokyo, 100-8162 Japan

Charge section: Lubricants Quality Assurance Group
(TEL:+81 3-6260-2004)**1.4. Emergency telephone number**Emergency telephone number: +81-3-6260-2004
(Contact Available time: From 9:00 to 17:30 GMT +9 hours)**2. Hazards identification**

Classification according to Regulation (EC) No. 1272/2008 (CLP)

2.1. Classification of the substance or mixture

Hazard category	Category
Flammable liquids	No Classification
Acute toxicity (oral)	No Classification
Acute toxicity (dermal)	No Classification
Aspiration hazard	No Classification

2.2. Label elements

Labeling according to Regulation (EC) No. 1272/2008 (CLP)

Hazard pictograms: Not applicable

Signal word: Not applicable

Hazard statement: Not applicable

Precautionary statements:

Prevention Do not handle until all safety precautions have been read and understood. (P202)

Wear protective gloves/protective clothing/eye protection/face protection. (P280)

Do not allow the eyes to become exposed to the product. Do not swallow the product.

Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product. (P270)

Response IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. (P301+P310)

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. (P301+P330+P331)

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

If the eyes are exposed to the product: Rinse the eyes with plenty of running water and immediately contact a physician.

IF ON SKIN: Wash with plenty of soap and water. (P302+P352)

Storage The product must be stored in a cool, well-ventilated location where it will not be exposed to direct sunlight.

Containers that have been opened must be tightly sealed.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

If there are any doubts about proper methods of handling the product, contact the point of purchase before proceeding with usage.

2.3. Other hazards

PBT or vPvB : Not applicable

3. Composition/information on ingredients

3.1. Substances Not Applicable

3.2. Mixtures

Ingredients and Concentration

Ingredient Name	Concentrationwt. %
Base Oil(s)	80-90
Additives	<20

4. First aid measures

4.1. Description of first aid measures

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. (P304+P340)
Cover the body with blankets to keep warm and quiet. If you feel unwell, seek medical advice.

Skin contact: Immediately flush skin with large amounts of water.
Wash contaminated clothing before reuse. (P363)
If skin irritation occurs: Get medical advice/attention. (P332+P313)

Eye contact: Rinse with clean water carefully for several minutes. Remove contact lenses if present and if removal is easy, then continue rinsing. Rinse for 15 minutes at a minimum and seek medical attention.

Ingestion: Do not induce vomiting. Drink water. Call a physician or poison control center immediately.

4.2. Most important symptoms and effects, both acute and delayed

No information for mixtures.

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

4.3. Indication of any immediate medical attention and special treatment needed

No information for mixtures.

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Mist of loaded liquid, dry chemicals, carbon dioxide, fire foam, and dry sand are effective.

Extinguishing media to avoid: Use of straight stream of water can cause a risk of spreading fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical: In some cases of fire, may release irritant gases.

When burnt, may generate carbon monoxide and other toxic gases.

Fire fighting: Spray water to the surrounding facilities for cooling.

Keep unauthorized persons off the site of occurrence of fire and the surroundings.

Even after extinction, cool containers thoroughly with plenty of water.

5.3. Advice for fire-fighters

Special protective equipment and precautions for fire fighters: Wear fire/flame resistant/retardant clothing. (P283)

Fight fire from windward direction while wearing protective equipment. If contact with skin is expected, wear impervious protective equipment and gloves.

Use air-breathing apparatus and protective clothing whenever necessary.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency measures

Wear protective equipment when working.

Remove nearby potential ignition sources immediately.

When mist is generated, use respiratory equipment to prevent inhalation of mist.

Do not touch or walk through spillage.

Pay attention to the site of spillage, which is slippery.

6.2. Environmental precautions

Prevent spreading of oil spill with earth and sand, sandbags, or other proper materials and use care not to allow the oil spill to flow to street drains, sewer systems, and rivers.

At sea, install oil spill containment booms to prevent spreading of spills and absorb with absorption mat or other proper materials.

6.3. Methods and material for containment and cleaning up

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

In case of spillage in small quantity, collect spillage by absorbing with earth, sand, sawdust, waste, or other proper materials.

In case of spillage in large quantity, enclose with embankment to prevent spreading of spillage and collect spillage in empty containers to the extent possible.

In case of spillage, immediately inform the organizations concerned of the spillage to prevent possible accidents and spreading of spillage.

Remove nearby potential ignition sources immediately and make fire-extinguishing agents available. Remove spillage completely, and ventilate and clean the site and the surroundings.

6.4. Reference to other sections

See section 8 for type of protective equipment.

See section 13 for instructions on disposal.

7. Handling and storage**7.1. Precautions for safe handling**

Technical measures:	Keep away from any possible contact with sparks, open flames, and high-temperature materials, and do not allow release of vapor without justification.
	Use pumps or other proper equipment for taking out from containers. Do not siphon with your mouth using a tube. Do not drink.
	When mist is generated, use respiratory equipment to prevent inhalation of mist.
	In case of vapor/mist dispersion, install a closed system, local ventilation system, and/or other proper equipment for the sources of vapor/mist generation.
	Avoid rough handling of containers such as falling, dropping, exposing to shock, and dragging.
Ventilation requirements:	Maintain adequate ventilation when handling indoors.
Precautions:	Wash hands and face thoroughly after handling.
	Be careful with fire.
Precautions for safe handling:	Avoid falling, dropping, exposing to shock, or dragging of containers.
	Wear protective gloves when opening containers to eliminate a risk of hand injury.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions:	Store in a well ventilated, cool, dry, dark place, protecting from direct sunlight and keeping away from any potential ignition sources and high-temperature materials.
	Store tightly stopped after use to prevent possible contamination with dust and moisture.
	Preferably store locked up in a proper storage area.

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

Safety adequate Use spill-proof containers that are free of damage/corrosion.
 container materials:

7.3. Specific end use(s)

General industrial application

8. Exposure controls/personal protection**8.1. Control parameters**

Ingredient Name	Japan Society for Occupational	ACGIH	
	Occupational Exposure Limits	TLV-STEL	TLV-TWA
Base Oil(s)	None established ppm, 3mg/m3 (Mineral Oil Mist)	None established ppm, None establishedmg/m3	None established ppm, 5mg/m3 (Mineral Oil Mist)

8.2. Exposure controls

Appropriate engineering controls: In case of mist generation, enclose the source of mist generation, or install a ventilation system.
 Install eye cleaning and body cleaning equipment near the handling site.

Respiratory protection: Not needed under normal conditions, but wear a gas mask (against organic gases) whenever required.

Hand protection: In case of prolonged or repeated exposure, wear oil-resistant hand protection.

Eye/face protection: In case of exposure to splashes, wear ordinary type goggles.

Skin protection: In case of handling over a prolonged period of time or in case of exposure to oil, wear oil-resistant, long-sleeved work clothing.

Hygiene measures: Take off contaminated clothing and wash thoroughly before reuse.
 Wash hands thoroughly after handling.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state: Liquid
 Form: Liquid
 Color: Light brown
 Odor: Slight odor
 Melting point/freezing point: Pour Point-40(°C)
 Initial boiling point and boiling range: Initial boiling point - End point No data
 Flash point: 222(°C)Cleveland Open Cup

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

Auto-ignition temperature: Estimate 200–410(°C)

Upper/lower flammability or explosive limits: Explosion Limit (1-7%)

Vapour density: No data.

Density(g/cm³): 0.869(15°C)

Solubility: water : Insoluble.

Partition coefficient: n-octanol/water: No data.

Decomposition temperature: No data.

Kinematic viscosity: >20.5(mm²/sec)(40°C)

10. Stability and reactivity**10.1. Reactivity**

Not Reactive

10.2. Chemical stability

Stable when stored or preserved in a dark place at room temperature.

10.3. Possibility of hazardous reactions

Keep away from any possible contact with strong oxidizing agents.

10.4. Conditions to avoid

Contact with incompatible hazard substances

Prolonged heating, open flames, and ignition sources

10.5. Incompatible materials

Use care to keep away from any possible contact with halogens, strong acids, alkalis, and acidifying substances.

10.6. Hazardous decomposition products

When burnt, may release carbon monoxide and other gases.

11. Toxicological information**11.1. Information on toxicological effects**

Product

Acute toxicity (oral):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Acute toxicity (dermal):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Acute toxicity (inhalation):	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Skin corrosion/irritation:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Serious eye damage/irritation:	For mixtures, hazard category was identified based on the classification criteria for mixtures.

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

Respiratory sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Skin sensitization:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Mutagenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Carcinogenicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Reproductive toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Target organ effect/Single exposure:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Target organ effect/Multi exposure:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Respiratory toxic:	For mixtures, hazard category was identified based on the classification criteria for mixtures.

11.2. Other information

Product

No information for mixtures.

Ingredient

Base Oil(s)

Acute toxicity (oral):	LD50: \geq 5000 mg/kg[rat]
Acute toxicity (dermal):	LD50: \geq 5000 mg/kg[rat]
Serious eye damage/irritation:	Practically None
Skin sensitization:	None Buehler method [guinea pig]
Mutagenicity:	Ames Test:Negative
Carcinogenicity:	EU:Category 2 : R45 need not apply. (NOTE L is Applicable), IARC:3

12. Ecological information**12.1. Toxicity**

Ecotoxicity

Fish acute toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Base Oil(s)	96hLC50: > 5000 mg/L[Oncorhynchus mykiss]
Algae acute toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Fish chronic toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.
Algae chronic toxicity:	For mixtures, hazard category was identified based on the classification criteria for mixtures.

12.2. Persistence and degradability

Persistence and degradability: No information for mixtures.

12.3. Bioaccumulative potential

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

Bioaccumulative potential : No information for mixtures.

12.4. Mobility in soil

Mobility in soil: No information for mixtures.

12.5. Results of PBT and vPvB assessment

Not applicable

12.6. Other adverse effects

Other impact : No information for mixtures.

13. Disposal considerations**13.1. Waste treatment methods**

Dispose of contents/container in accordance with local/regional/national/international regulations.

Every customer/user of the product should dispose of industrial waste on its own responsibility, otherwise it must rely on a company authorized by prefectural governor for treating industrial waste or a local public body involved in the disposal of industrial waste for proper disposal.

Before disposal of used container, remove contents completely.

13.2. Other information

No additional information

14. Transport information**14.1. UN Number:**

IATA UN number: Not applicable

IMDG UN number: Not applicable

14.2. UN proper shipping name:

IATA Proper shipping name: Not applicable

IMDG Proper shipping name: Not applicable

14.3. Transport hazard class(es):

IATA UN classification: Not applicable

IMDG UN classification: Not applicable

14.4. Packing group:

IATA Packing group: Not applicable

IMDG Packing group: Not applicable

14.5. Environmental hazards:

Marine pollutant: applicable

14.6. Special precautions for user:

Transport containers without causing any significant friction or shaking.

15. Regulatory information

SAFETY DATA SHEET

MSDS: A4176_E71EEN

Date Prepared: 2017/06/28

Date Revised:

Product Name: SUZUKI ECSTAR Marine FCW Semi Synthetic 10W40

**15.1. Safety, health and environmental regulations/legislation specific for the substance
EU regulations**

Korea (KECL) : All components are listed or exempted.
Australia (AICS) : All components are listed or exempted.
Canada (DSL) : All components are listed or exempted.
China (IECSC) : In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
EU (REACH) : In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.
New Zealand (NZIoC) : All components are listed or exempted.
USA (TSCA) : All components are listed or exempted.
Philippines (PICCS) : All components are listed or exempted.
Taiwan : In the case where one or more components are not listed or, even if listed, in the case of importing to the country or area concerned, an application or notification is required.

15.2. Chemical safety assessmentNot conducted

16. Other information

Disclaimer: We at JXTG Nippon Oil & Energy Corporation have prepared the copyrighted Safety Data Sheet to provide reference information on the hazardous chemical product of interest for our customers/users to ensure secure and safe handling.
We would like every customer/user of the product to refer to the information and understand the necessity of taking appropriate measures for the actual handling conditions on their own responsibilities for optimum practical application of the product of interest.
Consequently, the Safety Data Sheet is not intended to guarantee the safety of the product referenced to herein.