

Safety Data Sheet

Printing date 09/28/2015

Revised On 09/28/2015

1 Identification of the substance and manufacturer

Trade name: Yamalube Marine Spray Paint 04D Dark Bluish Gray Metallic 2
Distributed by Yamaha Motor Corporation U.S.A.

Product code: ACC-MRNPA-IT-4D

Manufacturer/Supplier: Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178
Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
Press. Gas H280 Contains gas under pressure; may explode if heated.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Repr. 2 H361 Suspected of damaging fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger
Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If skin irritation occurs: Get medical advice/attention.
If on skin: Wash with plenty of water.
If eye irritation persists: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Store in a well-ventilated place. Keep container tightly closed.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|------------|---------------------------------|--------|
| 67-64-1 | Acetone | 40.68% |
| 74-98-6 | propane | 15.75% |
| 108-88-3 | Toluene | 12.77% |
| 106-97-8 | n-butane | 9.25% |
| 108-10-1 | methyl isobutyl ketone | 2.16% |
| 107-87-9 | Methyl Propyl Ketone | 1.93% |
| 2807-30-9 | Glycol Ether EP | 1.67% |
| 7429-90-5 | Aluminum flake | 0.59% |
| 64742-47-8 | Mineral Spirits | 0.52% |
| 1330-20-7 | xylene (mix) | 0.31% |
| 28262-63-7 | ACRYLIC RESIN | 13.47% |
| 108-65-6 | PM acetate | 0.28% |
| 22464-99-9 | solid zirco drier | 0.22% |
| 64742-89-8 | VM&P Naphtha | 0.1% |
| 64742-95-6 | Solvent naphtha, light aromatic | 0.09% |

(Contd. on page 2)

Safety Data Sheet

Printing date 09/28/2015

Revised On 09/28/2015

Trade name: Yamalube Marine Spray Paint 04D Dark Bluish Gray Metallic 2
Distributed by Yamaha Motor Corporation U.S.A.

(Contd. of page 1)

| | | |
|-----------|------------------------------|-------|
| 136-52-7 | cobalt bis(2-ethylhexanoate) | 0.08% |
| 100-41-4 | ethyl benzene | 0.07% |
| 1333-86-4 | Carbon black | 0.06% |

4 First-aid measures

| | |
|--|--|
| After inhalation: | Supply fresh air; consult doctor in case of complaints. |
| After skin contact: | Remove contaminated clothing. Wash exposed area with soap and water. |
| After eye contact: | Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. |
| After swallowing: | Rinse mouth with water. Do not induce vomiting. |
| Most important symptoms and effects: | Dizziness |
| Indication of any immediate medical attention needed: | No further relevant information available. |

5 Fire-fighting measures

| | |
|---|--|
| Extinguishing agents: | CO2, extinguishing powder or water spray. Fight larger fires with water spray. |
| Special hazards: | Can form explosive gas-air mixtures. |
| Protective equipment for firefighters: | A respiratory protective device may be necessary. |

6 Accidental release measures

| | |
|---|--|
| Personal precautions, protective equipment and emergency procedures: | Use respiratory protective device against the effects of fumes/dust/aerosol. |
| Methods and material for containment and cleaning up: | Absorb liquid components with liquid-binding material. |

7 Handling and storage

| | |
|--------------------------------------|--|
| Precautions for safe handling | Use only in well ventilated areas. |
| Conditions for safe storage: | |
| Storage requirements: | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. |

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

| | |
|---------------------------|---|
| TLV (USA full disclosure) | Long-term value: 600 mg/m ³ , 250 ppm |
| PEL (USA) | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV (USA) | Short-term value: (1782) NIC-1187 mg/m ³ , (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m ³ , (500) NIC-250 ppm BEI |

74-98-6 propane

| | |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| TLV (USA) | refer to Appendix F |

108-88-3 Toluene

| | |
|---------------------------|---|
| TLV (USA full disclosure) | Short-term value: 500 mg/m ³ , 300 ppm Long-term value: 375 mg/m ³ , 200 ppm |
| PEL (USA) | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL (USA) | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV (USA) | Long-term value: 75 mg/m ³ , 20 ppm BEI |

106-97-8 n-butane

| | |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m ³ , 800 ppm |
| TLV (USA) | Short-term value: 2370 mg/m ³ , 1000 ppm |

108-10-1 methyl isobutyl ketone

| | |
|-----------|---|
| PEL (USA) | Long-term value: 410 mg/m ³ , 100 ppm |
| REL (USA) | Short-term value: 300 mg/m ³ , 75 ppm Long-term value: 205 mg/m ³ , 50 ppm |
| TLV (USA) | Short-term value: 307 mg/m ³ , 75 ppm Long-term value: 82 mg/m ³ , 20 ppm BEI |

107-87-9 Methyl Propyl Ketone

| | |
|-----------|--|
| PEL (USA) | Long-term value: 700 mg/m ³ , 200 ppm |
|-----------|--|

(Contd. on page 3)

Safety Data Sheet

Printing date 09/28/2015

Revised On 09/28/2015

Trade name: Yamalube Marine Spray Paint 04D Dark Bluish Gray Metallic 2
 Distributed by Yamaha Motor Corporation U.S.A.

(Contd. of page 2)

| | |
|-----------|---|
| REL (USA) | Long-term value: 530 mg/m ³ , 150 ppm |
| TLV (USA) | Short-term value: 529 mg/m ³ , 150 ppm |

2807-30-9 Glycol Ether EP

| | |
|---------------------------|---|
| TLV (USA full disclosure) | Short-term value: 86 mg/m ³ , 20 ppm |
| | Long-term value: 86 mg/m ³ , 20 ppm |

Ingredients with biological limit values:**67-64-1 Acetone**

| | |
|-----------|----------------------------------|
| BEI (USA) | 50 mg/L |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: Acetone (nonspecific) |

108-88-3 Toluene

| | |
|-----------|---------------------------------------|
| BEI (USA) | 0.02 mg/L |
| | Medium: blood |
| | Time: prior to last shift of workweek |
| | Parameter: Toluene |

| | |
|--|--------------------|
| | 0.03 mg/L |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: Toluene |

| | |
|--|--|
| | 0.3 mg/g creatinine |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: o-Cresol with hydrolysis (background) |

108-10-1 methyl isobutyl ketone

| | |
|-----------|--------------------|
| BEI (USA) | 1 mg/L |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: MIBK |

Hygienic protection: Immediately remove all soiled and contaminated clothing.
Wash hands after use.

Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties**General Information:**

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value: Not determined.

Melting point/Melting range: Undetermined.

Boiling point: -44 °C (-47 °F)

Flash point: -19 °C (-2 °F)

Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol %

Upper Explosion Limit: 10.9 Vol %

Vapor pressure: 40 PSI 2750 hPa

Vapor Pressure: 40 PSI, 2750 hPa

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density: Not determined.

Evaporation rate: Not applicable.

Partition coefficient: n-octonal/water: Not determined.

Solubility: Not determined.

Viscosity: Not determined.

Dynamic: Not determined.

Kinematic: Not determined.

VOC content: 543.8 g/l / 4.54 lb/gl

VOC content (less exempt solvents): 44.9 %

MIR Value: 1.15

Solids content: 14.7 %

(Contd. on page 4)

Safety Data Sheet

Printing date 09/28/2015

Revised On 09/28/2015

Trade name: Yamalube Marine Spray Paint 04D Dark Bluish Gray Metallic 2
Distributed by Yamaha Motor Corporation U.S.A.

(Contd. of page 3)

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Conditions to avoid: No further relevant information available.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

| | | |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

108-10-1 methyl isobutyl ketone

| | | |
|------------|----------|---------------------|
| Oral | LD50 | 2100 mg/kg (rat) |
| Dermal | LD50 | 16000 mg/kg (rab) |
| Inhalative | LC50/4 h | 8.3-16.6 mg/l (rat) |

1330-20-7 xylene (mix)

| | | |
|------------|----------|------------------|
| Oral | LD50 | 8700 mg/kg (rat) |
| Dermal | LD50 | 2000 mg/kg (rbt) |
| Inhalative | LC50/4 h | 6350 mg/l (rat) |

108-65-6 PM acetate

| | | |
|------------|----------|------------------|
| Oral | LD50 | 8500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat) |

64742-95-6 Solvent naphtha, light aromatic

| | | |
|------------|----------|-------------------|
| Oral | LD50 | >6800 mg/kg (rat) |
| Dermal | LD50 | >3400 mg/kg (rab) |
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |

100-41-4 ethyl benzene

| | | |
|--------|------|-------------------|
| Oral | LD50 | 3500 mg/kg (rat) |
| Dermal | LD50 | 17800 mg/kg (rbt) |

1333-86-4 Carbon black

| | | |
|------|------|-------------------|
| Oral | LD50 | 10000 mg/kg (rat) |
|------|------|-------------------|

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

| | | |
|----------|------------------------|----|
| 108-88-3 | Toluene | 3 |
| 108-10-1 | methyl isobutyl ketone | 2B |

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Toxicity
Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Recommendation: Completely empty cans should be recycled.

14 Transport information

| | |
|------------------|---|
| UN-Number | UN1950 |
| DOT | N/A |
| DOT | Consumer Commodity ORM-D Aerosols, flammable |

Transport hazard class(es):
Class 2.1

(Contd. on page 5)

Safety Data Sheet

Printing date 09/28/2015

Revised On 09/28/2015

Trade name: Yamalube Marine Spray Paint 04D Dark Bluish Gray Metallic 2
 Distributed by Yamaha Motor Corporation U.S.A.

(Contd. of page 4)

Label 2.1
ADR Class 2 5F Gases
Marine pollutant: No
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
Quantity limitations On passenger aircraft/rail: 75 kg
 On cargo aircraft only: 150 kg

ADR Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

IMDG Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
 Not permitted as Excepted Quantity

IATA Packaging Group: --
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene
 108-10-1 methyl isobutyl ketone

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

108-10-1 methyl isobutyl ketone
 100-41-4 ethyl benzene
 1333-86-4 Carbon black

California Proposition 65 chemicals known to cause developmental toxicity:

108-88-3 Toluene

EPA:

| | | |
|----------|------------------------|----|
| 67-64-1 | Acetone | I |
| 108-88-3 | Toluene | II |
| 108-10-1 | methyl isobutyl ketone | I |

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Date of preparation / last revision 09/28/2015 / -

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 EINECS: European Inventory of Existing Commercial Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 ISO: International Organisation for Standardisation
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health
 TSCA: Toxic Substances Control Act
 CPSC: Consumer Product Safety Commission
 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1
 Press. Gas: Gases under pressure: Liquefied gas
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
 Repr. 2: Reproductive toxicity, Hazard Category 2
 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
 STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2