

T R INDUSTRIES -- SEAPOWER CLEANER WAX, SG-1 -- 7930-00N053971

===== Product Identification =====

Product ID:SEAPOWER CLEANER WAX, SG-1

MSDS Date:07/01/1989

FSC:7930

NIIN:00N053971

MSDS Number: BVXHD

=== Responsible Party ===

Company Name:T R INDUSTRIES

Address:11022 VALCAN ST

City:SOUTHGATE

State:CA

ZIP:90280-0893

Country:US

Info Phone Num:213-923-0838

Emergency Phone Num:213-664-2121;800-424-9300(CHEMTREC)

Preparer's Name:R. L. DORY

CAGE:0E5N9

=== Contractor Identification ===

Company Name:T R INDUSTRIES

Address:11022 VALCAN ST

Box:City:SOUTHGATE

State:CA

ZIP:90280-0893

Country:US

Phone:213-923-0838

CAGE:0E5N9

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA, HEAVY STRAIGHT RUN; (STODDARD SOLVENT)

CAS:64741-41-9

Fraction by Wt: 40-50%

OSHA PEL:300 PPM

ACGIH TLV:300 PPM

Ingred Name:TURPENTINE

CAS:8006-64-2

RTECS #:Y08400000

Fraction by Wt: 5%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

Ingred Name:ISOPROPYL ALCOHOL

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 5%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM;500 PPM STEL

Ingred Name:MINERALS (MFR INVALID CAS # 7531-86-9)

Fraction by Wt: 5%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:MORPHOLINE

CAS:110-91-8

RTECS #:QD6475000

Fraction by Wt: 0.75%
OSHA PEL:20 PPM, S
ACGIH TLV:20 PPM, S

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYE: PRODUCT MAY BE AN EYE IRRITANT.
SKIN: PROLONGED SKIN CONTACT MAY RESULT IN IRRITATION AND/OR
DERMATITIS. HARMFUL IF SWALLOWED.
Explanation of Carcinogenicity:NOT RELEVANT.
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:GENTLY FLUSH W/LRG QTYS OF WATER FOR AT LST 15 MINS. SEEK
MED ATTN IMMED. SKIN:REMOVE ANY CONTAMD CLTHG. WASH W/SOAP & LRG
QTYS OF WATER. SEEK MED ATTN IF IRRIT.INHAL: IF BRTHG DFCLTYS,
DIZZ, OR L IGH-HEADEDNESS OCCUR WHEN WORKING IN AREAS W/HIGH VAP
CONC, MOVE TO OUTSIDE AIR IMMED. IF BRTHG STOPS, BEGIN ARTF RESP &
SEEK IMMED MED ATTN. INGEST: SEEK MED ATTN IMMED. DO NOT INDUCE
VOMIT (SUPDAT)

===== Fire Fighting Measures =====

Flash Point:>100F,>38C
Extinguishing Media:USE FOAM, CARBON DIOXIDE OR DRY CHEMICAL FIRE
FIGHTING APPARATUS.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT . AVOID SPREADING BURNING LIQUID WITH WATER.
CONTACT FIRE DEPT IMMEDIATELY.
Unusual Fire/Explosion Hazard:KEEP WORK AREAS FREE OF HOT METAL
SURFACES AND OTHER SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:STAY UPWIND AND AWAY FROM SPILL UNLESS WEARING
APPROPRIATE PROTECTIVE EQUIPMENT. STOP AND/OR CONTAIN SPILL IF IT
CAN BE DONE SAFELY. KEEP ALL SOURCES OF IGNITION AWAY.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT CONTAINERS COOL, DRY AND
AWAY FROM SOURCES OF IGNITION. USE AND STORE WITH ADEQUATE
VENTILATION.
Other Precautions:PERSONNEL SHOULD AVOID INHALATION OF VAPORS. SHOULD
CONTACT BE MADE, REMOVE SATURATED CLOTHING AND FLUSH WITH WATER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE OF RESPIRATORY PROTECTION DEPENDS ON VAPOR
CONCENTRATION TIME-WEIGHTED TLV. USE A NIOSH/MSHA APPROVED
RESPIRATOR/GAS MASK WITH APPROPRIATE CARTRIDGES AND CANISTER, OR
SUPPLIED AIR EQUIPMENT, DEPEN DING ON AIRBORNE CONCENTRATION.
Ventilation:IF GEN MECH VENT PROVES INADEQUATE TO MAINTAIN SAFE VAP
CONCS, SUPP LOC EXHST MAY BE REQD.OTHER SPEC PRECS,SUCH (SUPDAT)
Protective Gloves:HEAVY RUBBER GLOVES.

Eye Protection:ANSI APPROVED CHEM WORKERS GOGG .
Other Protective Equipment:IMPERMEABLE APRONS, AVAILABILITY OF EYE
WASHES AND SAFETY SHOWER ARE RECOMMENDED.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRST AID PROCEDURES: UNLESS DIRECTED BY PHYSICIAN. VENTILATION: AS
RESPIRATORY PROTECTION, MAY BE REQUIRED IF VAPOR CONCENTRATIONS
CANNOT BE REDUCED TO BELOW TLV BY VENTILATION.

===== Physical/Chemical Properties =====

HCC:F4
Vapor Density:HVR/AIR
Spec Gravity:LIGHTER/WATER
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:PRODUCT IS MILKY WHITE WITH CHARACTERISTIC ODOR.
Percent Volatiles by Volume:65

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE.
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:THERMAL DECOMPOSITION IN PRESENCE OF
AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF PRODUCT IN ACCORDANCE WITH APPLICABLE
LOCAL, COUNTY, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.