

Stability	Unstable		Conditions to Avoid
	Stable	X	None known

Incompatibility (*Materials to Avoid*)  
Strong oxidizers

Hazardous Decomposition or Byproducts

N/A

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	None known

### Section VI — Health Hazard Data

Route(s) of Entry: Inhalation? Skin?  Ingestion?

Health Hazards (*Acute and Chronic*)

Vapors and mist can irritate nose, throat and lungs. Slight irritation to skin. Contact of product to eyes may cause slight irritation.

Carcinogenicity: NONE NTP? NE IARC Monographs? NE OSHA Regulated? NE

Signs and Symptoms of Exposure

Vapors and mist can irritate nose, throat and lungs. Slight irritation to skin. Contact of product to eyes may cause slight irritation.

Medical Conditions

Generally Aggravated by Exposure Substantially irritating to eyes. Slightly irritating to skin.

Emergency and First Aid Procedures

If Swallowed: Drink 2 glasses of water and contact physician. If in Eyes: Flush with fresh water for 15 minutes. If on Skin: Wash thoroughly with soap and water.

### Section VII — Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled

Ventilate area. Remove source of spill. Remove spill with inert absorbent. NOTE: This product is not a hazardous waste under RCRA regulations.

Waste Disposal Method

Dispose material as non-hazardous paint product according to local regulations.

Precautions to Be Taken in Handling and Storing

Storage temperature range: Minimum 34°F (1°C) to 120°F (49°C). KEEP FROM FREEZING.

Other Precautions

### Section VIII — Control Measures

Respiratory Protection (*Specify Type*)

MSHA/NIOSH-approved or equivalent if exposure limits are to be exceeded (spraying of product)

Ventilation	Local Exhaust	Special
	<input checked="" type="checkbox"/>	Ventilate area of contaminant release (spill)
	Mechanical (General)	Other

Protective Gloves Rubber/latex Eye Protection Safety/splash goggles

Other Protective Clothing or Equipment None needed

Work/Hygienic Practices

Wash hands thoroughly with soap and water after handling.

# Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

# U.S. Department of Labor

Occupational Safety and Health Administration  
(Non-Mandatory Form)

Form Approved  
OMB No. 1218-0072



IDENTITY (As Used on Label and List)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Amazon's Teak Lustre (TL-350, TL-352)

## Section I

Manufacturer's Name Marine Development & Research Corp.	Emergency Telephone Number 1-800-535-5053
Address (Number, Street, City, State, and ZIP Code) 2116 Merrick Avenue, Suite 4001	Telephone Number for Information 1-516-546-1162
Merrick, NY 11566	Date Prepared October 20, 2008
	Signature of Preparer (optional)

## Section II — Hazardous Ingredients/Identity Information NE = Negligible

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Acrylic Resins (CAS# Proprietary)	NE	NE		
Organo-silicone (CAS# Proprietary)	NE	NE		
Dipropylene glycol monomethyl (CAS#34590-94-8)	NE	NE		
Propylene glycol n-propyl ether (CAS#1569-01-3)	NE	NE		
Polyethylene wax (CAS# 68441-17-8)	NE	NE		
Polyether modified dimethylpolysiloxane (CAS# Proprietary)	NE	NE		

HMIS Ratings = Health:0 Flammability:0 Reactivity:0 (Ratings based on 0 - 4 scale)

## Section III — Physical/Chemical Characteristics

Boiling Point	192°F - 396°F	Specific Gravity (H <sub>2</sub> O = 1)	1.36
Vapor Pressure (mm Hg.)	Greater than 1	Melting Point	Variable
Vapor Density (AIR = 1)	Greater than 1	Evaporation Rate (Butyl Acetate = 1)	Slower than ether
Solubility in Water	Dilutable	pH: 7-9	VOC Content: .393#/gallon = 47 grams/liter
Appearance and Odor	Milky white liquid (dries clear); mild odor	VHAP Content: 0	#VOC/Gallon Solids: 0.98

## Section IV — Fire and Explosion Hazard Data N/A = Not Applicable

Flash Point (Method Used) N/A (Non-flammable, non-combustible)	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media Carbon dioxide; dry chemical; water fog			
Special Fire Fighting Procedures Water may be used to cool closed containers to prevent pressure build-up.			

Unusual Fire and Explosion Hazards  
Material will not support combustion unless the water has evaporated.