

MOELLER MARINE MOTOR COLORS

A fast drying spray paint that provides durable indoor and outdoor protection. Resistant to the effects of weather and many chemicals. Resists abrasion and heat (250F). Bare surfaces or rusted metal surfaces should first be primed to ensure proper adhesion.

Suggested Uses:

Home
Automotive
Industrial
Marine
Construction

Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flash point	-4F
Specific Gravity	0.86
Solids Content	Glosses: ~15% Flats: ~15% Metallics: ~13%
MIR value	Glosses: 0.86, cannot exceed 0.95 Clear: 0.82, cannot exceed 0.85 Metallics: 1.17, cannot exceed 1.25
HAPs content	Glosses: ~13% Clear: ~25% Metallics: ~30%
Storage Temperature	40-100F
Application Temperature	50-90F
Durability	Good
Abrasion Resistance	Good
Gasoline Resistance	No
Heat Resistance	250F
Resin System	Acrylic lacquer
Shelf life	Guaranteed for 2 years

Dry Time*:

Tack free	5 minutes
To recoat	20 minutes

*At 72F, 50% humidity,
1.5 mil thickness

**Curing/Recoat time is extended with
multiple coats and excessively thick coats**

Gloss*: High Gloss, >80
Semi-Gloss, 10-20
Flat, <15

*as measured on a 60 degree gloss meter