

## HI-HEAT PAINT

### #025811 White

A heat resistant spray paint designed to withstand temperatures up to 1200°F (648° C) on a continuous basis. Creates a porcelain-like bond at high temperatures. Resists peeling, loss of adhesion, and blistering. Must be heat cured at a minimum temperature of 400°F for two hours. Do not use a primer.

---

#### Suggested Uses:

Headers  
Manifolds  
Mufflers  
Exhaust Pipes  
Diesel Stacks  
Furnaces

---

#### Packaging:

Cans per case	6
Shipping weight per case	7 lbs.
Container	16 fluid ounce can
Label weight	12 ounces (340 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

---

#### Properties:

Coverage	Up to 15 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.82
Solids Content	21%
MIR value	1.48, cannot exceed 1.85
HAPs content	26%
Storage Temperature	40-90F
Application Temperature	50-100F
Durability	Excellent
Abrasion Resistance	Excellent
Gasoline/Oil Resistance	Yes
Heat Resistance	1200F
Resin System	Silicone
Shelf life	Guaranteed for 2 years

---

#### Dry Time\*:

To touch	20 minutes
Hard Cure	<b>Must be heated to 400 F for two hours</b>

\*At 72F, 50% humidity,  
1.5 mil thickness

\*\*Curing/Recoat time is extended with  
multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <15

\*as measured on a 60 degree gloss meter

---